



SCP SEALER

PRODUCT DESCRIPTION

Scientific Concrete Polishing SEALER is designed to be a stain resistant, high gloss sealer adding hardness and chemical resistance to the concrete. This reactive penetrating product forms an insoluble chemical bond to produce a dense sealed surface, with superior hardness, and slip resistance.

STANDARD COLORS: Milky White

CURE SCHEDULE (70°)

TACK FREE (DRY TO TOUCH)	40-70 minutes
RECOAT OR TOPCOAT	1 hour
LIGHT FOOT TRAFFIC	40-70 minutes
FULL CURE	3 days

COVERAGE

COVERAGE RATE:	1500-2500 sq ft/ gallon
PACKAGING INFORMATION:	1, 5 and 55 Gallon Kits

LIMITATIONS

*Increased amount of stain-resistance *Allows vapor transmission *Can be applied to fresh concrete *Ease of use *Quick drying *Self-polishing

INSTRUCTIONS

PRODUCT APPLICATION: Apply SEALER at 600 ft² per gallon with a pump sprayer and microfiber pad. One hour is recommended between multiple SEALER applications. Too much product applied will result in improper curing and possible white discoloration. After SEALER has fully cured use a high speed burnisher to improve surface gloss. Don't allow water on the surface for 24 hours. If you apply more than one coat of SCP Sealer you will get a more uniform look.

SURFACE PREPARATION: Refer to the SCP Training manual and the ICRI standards for the proper surface preparation. Preparation methods will vary depending on application methods.

CLEANUP: Use soap and water.

FLOOR CLEANING: Caution! Some cleaners may affect the color of the floor installed. Test each cleaner in a small area, utilizing your cleaning technique. If no ill effects are noted, you can continue to clean with the product and process tested. Using a pH cleaner is recommended when cleaning floors with applied product.

RESTRICTIONS: Restrict the use of the floor to light traffic and non-harsh chemicals until the coating is fully cured (see technical data under full cure). It is best to let the floor remain dry for the full cure cycle.

NOTICE TO BUYER: DISCLAIMER OF WARRANTIES AND LIMITATIONS ON OUR LIABILITY

Scientific Concrete Polishing (Division of Incredible Products, LLC), warrants that all products are assembled under rigorous quality assurance specifications and that all information supplied is exact. All information supplied is not to be taken as a warranty, but for you to conduct your own test to determine if the given product is suitable for your distinct purpose. The following list of properties should not be interpreted as specifications. CONVEYED OR SUGGESTED, NO WARRANTY IS BUILT UPON ANY DISCOVERED RESULTS OR INFORMATION YOU WILL OBTAIN DURING USE. CONVEYED OR SUGGESTED NO WARRANTY IS BUILT THAT THE GIVEN PRODUCT SHALL BE MARKETABLE OR THAT THE GIVEN PRODUCT WILL BE FIT FOR ANY DISTINCT PURPOSE. NO WARRANTY IS BUILT UPON SAID INFORMATION OR THAT THE GIVEN PRODUCT WILL NOT INFRINGE UPON ANY PATENT. Scientific Concrete Polishing is NOT liable for, direct or indirect, inadvertent or consequential damages. Scientific Concrete Polishing liability is and will only be limited to the net selling price of our products or, at our discretion, the replacement of our products. Upon delivery of our products, your acceptance means that you accept all terms of this warranty even if the other documents and or purchase orders stray from the terms of this warranty. No representative, on our behalf, is permitted to make any representation, warranty, or assume liability with any sale of our products. OUR PRODUCTS CONTAIN CHEMICALS THAT CAN CAUSE SERIOUS PHYSICAL INJURY. BEFORE THE USE OF OUR PRODUCTS, READ ALL MATERIAL AND FOLLOW ALL LISTED PRECAUTIONS TO AVOID ANY BODILY HARM.